


PTM-SP 3X10



MAGNETICALLY DRIVEN, SINGLE-STAGE SELF-PRIMING REGENERATIVE TURBINE



- ☑ Self-Priming Regenerative Turbine Pump
- ☑ Up to 12m³/h (200l/min) flow
- ☑ Up to 52m head
- ☑ Available with threaded or flanged connections
- ☑ No metal in contact with pumped liquid
- ☑ Available in Polypropylene or PVDF

SPECIFICATION


FEATURES

Temp: Max 100°C
 Pressure: 10 Bar (System)
 Connections: PN16 Flange
 ANSI 150 Flange
 BSP Threaded

WETTED MATERIALS

Front Cover: PP or PVDF
 O Ring: EPDM or Viton
 Impeller: PVDF
 Shaft: Ceramic
 Bearings: PTFEC
 Rear Housing: PP or PVDF

SPARES



REF	DESCRIPTION	MATERIAL	REF	DESCRIPTION	MATERIAL
10	Rear Casing (INCL 75D)	PP or PVDF	62R	Rear Ring	PP or PVDF
20	Ext. Magnet	Neodym. / Steel	70	Shaft (INCL 75D)	Ceramic
30	Int. Magnet (INCL 75B+75C)	PP or PVDF / CoSm	75	Sleeve Bearings (A+B+C+D)	PTFEC
40	Impeller	PVDF	78	Bracket (200-130-24)	Cast Iron
50	O Ring	Viton or EPDM	85	Pump Head (INCL. 75A)	PP or PVDF
62F	Front Ring	PP or PVDF			



March May Ltd, Howard Road, Eaton Socon, St. Neots, Cambridgeshire, PE19 8NZ, UK




Tel: +44 (0) 1480 214444 Fax: +44 (0) 1480 405336 E-mail: sales@marchmay.co.uk Website: www.marchmay.co.uk

PTM-SP 3X10



MAGNETICALLY DRIVEN, SINGLE-STAGE REGENERATIVE TURBINE

PERFORMANCE



March May Ltd, Howard Road, Eaton Socon, St. Neots, Cambridgeshire, PE19 8NZ, UK


Tel: +44 (0) 1480 214444 Fax: +44 (0) 1480 405336 E-mail: sales@marchmay.co.uk Website: www.marchmay.co.uk

PTM-SP 3X10




MAGNETICALLY DRIVEN, SINGLE-STAGE REGENERATIVE TURBINE

DIMENSIONS



MODEL	DNs / I		DNd / Q		A	B	C	D	E	F	G	L	M	N	O	P	R	S	T	U
	mm	Gas	mm	Gas																
2.5 x 7.5	25	1"	25	1"	191	240	155	193	136	12	49	270	209	73	227	200	152	255	4	273
2.5 x 8	25	1"	25	1"	191	240	155	193	136	12	49	270	209	73	227	200	152	255	4	273
3 x 10	32	1 1/4"	32	1 1/4"	245	305	250	290	200	16	60	402	255	71	260	300	170	308	22	315

N° F fori-holes-trous ØG



DN	UNI PN 16				
	D	C	A	F	G
25			75	4	14-16
32			100	4	16-18

Ø	ANSI 150 RF				
	D	C	A	F	G
1"			69.8	4	14-16
1 1/4"			98.4	4	16-18



March May Ltd, Howard Road, Eaton Socon, St. Neots, Cambridgeshire, PE19 8NZ, UK

Tel: +44 (0) 1480 214444 Fax: +44 (0) 1480 405336 E-mail: sales@marchmay.co.uk Website: www.marchmay.co.uk